



Today's Date: _____


Business Name: _____


Shipping Address: _____


City: _____ State: _____ Zip: _____


Customer Name or PO Number: _____


HOW MANY?


CHIMNEY PIPE		Size	Qty. 6"	Qty. 8"
	5" to 8" diameters. Stainless steel inner walls. Outer casing in galvalume or stainless steel. 6", 9" and 18" lengths available in black outer-casings. Length is actual size. 1.5" are lost per section in make up. • 2" Clearance to combustibles. • 6" ID/OD=6"/8" • 8" ID/OD=8"/10"	6"	DT6-9402	DT8-9602
		9"	DT6-9408	DT8-9608
		12"	DT6-9403	DT8-9603
		18"	DT6-9404	DT8-9604
		24"	DT6-9405	DT8-9605
		36"	DT6-9406	DT8-9606
		48"	DT6-9407	DT8-9607

LOCKING BANDS		Qty. 6"	Qty. 8"
	Extra security at pipe, elbow and tee joints. Optional	DT6-9401	DT8-9601


ELBOW KITS		Item	Qty. 6"	Qty. 8"
	Kits include: 2 elbows and 1 elbow strap. 15° or 30° elbows swivel on 5" to 8" diameters. Stainless steel inner wall. Outer-casing in galvalume. Strap is used to support the chimney where an offset is required.	15°	DT6-9464Kit	DT8-9664Kit
		30°	DT6-9466Kit	DT8-9666Kit
		Strap	DT6-9460	DT8-9660


TEES & TEE SUPPORTS		Item	Qty. 6"	Qty. 8"
	Tees: For through-the-wall installations. Tee Supports: Use as a wall support for tee and chimney. Use of straps is optional. Supports up to 50' of DuraTech chimney without straps, and 70' of DuraTech chimney with straps. Finishing Collar: Decorative piece. Finishes off the end of DuraTech pipe. Provides proper connection to stovepipe when an adapter is used.	Tee w/Cap	DT6-9467SS	DT8-9667SS
		Support (Galv.)	DT6-9472GA	DT8-9672GA
		Support (SS)	DT6-9472SS	DT8-9672SS
		Finishing Collar	DT6-9455	DT8-9655


WALL THIMBLES		Type	Qty. 6"	Qty. 8"
	For passing chimney through wall.	Regular	DT6-9443	DT8-9643
		Exterior	DT6-9443SS	DT8-9643SS


WALL STRAPS		Type	Qty. 6"	Qty. 8"
	Use to support chimney 5-8" required every 8 ft.	Galv.	DT6-9468GA	DT8-9668GA
		SS	DT6-9468SS	DT8-9668SS

HOW MANY?

SUPPORTS & COLLARS		Size	Qty. 6"	Qty. 8"
	Square Ceiling Support Boxes: Supports up to 60 ft. of chimney. Use with flat or cathedral ceilings, in 11", 24" or 36" lengths. Includes trim collar. Flat: Designed for installation in flat ceilings only. Supports up to 60 ft. of pipe. Round: 5"-8" diameters support up to 60 ft. of chimney. Use only for a flat ceiling. Roof: Supports DuraTech chimney and allows it to extend down from the ceiling. Adjustable to different roof pitches. Trim Collar for Round or Roof Support Box: Conceals gap between chimney pipe and ceiling cut-out. Trim Collar for round ceiling support box comes in Round or Square.	Square 11"	DT6-9438A	DT8-9638A
		Square 24"	DT6-9438B	DT8-9638B
		Square 36"	DT6-9438D	DT8-9638D
		Flat	DT6-9444	DT8-9644
		Round	DT6-9445	DT8-9645
		Roof	DT6-9463	DT8-9663
		Trim Collar for Round (Round)	DT6-9345TR	DT8-9545TR
		Trim Collar for Round (Square)	DT6-9345TS	DT8-9545TS
		Trim Collar for Roof (0/12-3/12)	DT6-9448A	DT8-9648A
		Trim Collar for Roof (4/12-6/12)	DT6-9448B	DT8-9648B
		Trim Collar for Roof (7/12-9/12)	DT6-9448C	DT8-9648C
		Trim Collar for Roof (10/12-12/12)	DT6-9448D	DT8-9648D

ATTIC INSULATION SHIELDS		Qty. 6"	Qty. 8"
	Required if chimney passes through an attic.	DT6-9446	DT8-9646

RADIATION SHIELDS		Type	Qty. 6"	Qty. 8"
	Firestop: Install when chimney passes through a floor or ceiling without a support box. Roof: Optional. Install where a chimney passes through a roof. Required for some zero clearance fireplaces	Firestop	DT6-9447	DT8-9647
		Roof	DT6-9489	DT8-9689

FIRESTOPS		Qty. 6"	Qty. 8"
	Encloses the top of a chase while providing ventilation air passage to the chase.	DT6-9456	DT8-9656

STOVE PIPE ADAPTERS		Type	Qty. 6"	Qty. 8"
Dura DVL close clearance chimney adapters and DuraBlack snap-lock adapters available.	Dura-DVL	DVL/DB-8674	DVL/DB-8874	
	Dura-Black	DB6689	DB6889	



Today's Date: _____

Business Name: _____

Shipping Address: _____

City: _____ State: _____ Zip: _____

Customer Name or PO Number: _____

HOW MANY?

FLASHINGS & STORM COLLARS		Type	Qty. 6"	Qty. 8"
<p>Flashing: Use with a Storm Collar to weather proof the penetration of chimney pipe through the roof. Flat or adjustable. Also available in dead soft aluminum.</p> <p>Storm Collar: Fits over flashing to provide a water tight seal.</p>	Adjustable Flashing 0/12-6/12	DT6-9449	DT8-9649	
	Adjustable Flashing 7/12-12/12	DT6-9450	DT8-9950	
	Adjustable Flashing 13/12-18/12	DT6-9452	DT8-9652	
	Adjustable Flashing 19/12-24/12	DT6-9481	DT8-9648B	
	Storm Collar	DT6-9359	DT8-9681	


HOW MANY?

ANCHOR PLATES		Qty. 6"	Qty. 8"
<p>Use as a base plate for attaching DuraTech pipe to zero-clearance or masonry fireplaces.</p>	DT6-9441	DT8-9641	

CHIMNEY CAPS		Product	Qty. 6"	Qty. 8"
<p>Keeps rain, snow, and leaves out of chimney. Spark arrestor screen included.</p>	Chimney Cap	DT6-9484	DT8-9684	
	Extra Spark Arrestor	DT6-9482	DT8-9682	

EXTENDED ROOF BRACKETS		Qty. 6"	Qty. 8"
<p>Supports chimney above roof. Required every 5 ft. for 5-8" chimney.</p>	DT6-9465	DT8-9665	

OFFSET CHART



SIZE		6", 8" Diameter	
Elbow Angle from Vertical	Chimney Length Between Elbows	Offset inches	Rise inches
15°	0"	2"	16 1/2"
15°	6"	3 3/4"	21 1/4"
15°	9"	4"	24 1/2"
15°	12"	4 3/4"	27"
15°	18"	6 1/4"	32 3/4"
15°	24"	8"	38 1/2"
15°	36"	11"	50 1/4"
15°	48"	14 1/4"	61 3/4"

SIZE		6", 8" Diameter	
Elbow Angle from Vertical	Chimney Length Between Elbows	Offset inches	Rise inches
30°	0"	4"	15 3/4"
30°	6"	6 1/4"	20"
30°	9"	7 3/4"	22 5/8"
30°	12"	9 1/4"	25 1/4"
30°	18"	12 1/4"	30 1/4"
30°	24"	15 1/4"	35 1/2"
30°	36"	21 1/4"	46"
30°	48"	27 1/4"	56 1/4"

Ordered By: _____ Initials: _____

Print Name



Phone: **301-740-3488** Fax: **301-740-3489**
 8045 Snouffer School Rd., Gaithersburg, MD 20879
www.regionalchimneysupply.com